



Bearing No.	Boundary Dimensions (mm)							Basic Load Rating (kN)		Weight (kg)
	d	D	B	S	C	r _s min	Ds	Cr	Cor	
UC 204	20	47	31	12.7	17	1.0	M6×0.75	9.88	6.65	0.16
UC 205	25	52	34	14.3	17	1.0	M6×0.75	10.8	7.88	0.22
UC 206	30	62	38.1	15.9	19	1.0	M6×0.75	15.0	11.2	0.35
UC 207	35	72	42.9	17.5	20	1.1	M8×1.0	19.8	15.2	0.52
UC 208	40	80	49.2	19	21	1.1	M8×1.0	22.8	18.2	0.70
UC 209	45	85	49.2	19	22	1.1	M8×1.0	24.5	20.8	0.74
UC210	50	90	51.6	19	23	1.1	M10×1	27.0	23.2	0.83
UC 211	55	100	55.6	22.2	24	1.5	M10×1	43.4	29.2	0.974
UC 212	60	110	65.1	25.4	26	1.5	M10×1	52.5	35.9	1.47
UC 213	65	120	65.1	25.4	27	2.0	M10×1.25	44.0	34.0	1.71
UC 214	70	125	74.6	30.2	29	2.0	M12×1.5	46.8	37.5	2.06
UC 215	75	130	77.8	33.3	30	2.0	M12×1.5	50.8	41.2	2.22
UC 216	80	140	82.6	33.3	32	2.5	M12×1.5	55.0	44.8	2.82
UC 217	85	150	85.7	34.1	34	2.5	M12×1.5	64.0	53.2	3.38
UC 218	90	160	96	39.7	36	2.5	M12×1.5	73.8	60.5	4.34
UC 305	25	62	38	15	21	1.1	M6×0.75	17.2	11.2	0.44
UC 306	30	72	43	17	23	1.1	M6×0.75	20.8	14.2	0.56
UC 307	35	80	48	19	25	1.5	M8×1.0	25.8	17.8	0.71
UC 308	40	90	52	19	27	1.5	M10×1.25	31.2	22.2	1.00
UC 309	45	100	57	22	30	1.5	M10×1.25	40.8	29.8	1.28
UC 310	50	110	61	22	32	2.0	M12×1.5	47.5	35.5	1.65
UC 311	55	120	66	25	34	2.0	M12×1.5	55.2	41.8	2.07
UC 312	60	130	71	26	36	2.1	M12×1.5	62.8	48.5	2.59
UC 313	65	140	75	30	38	2.1	M12×1.5	72.2	56.5	3.15
UC 314	70	150	78	33	40	2.1	M12×1.5	80.2	63.2	3.83
UC 315	75	160	82	32	42	2.1	M14×1.5	87.2	71.5	4.59
UC 316	80	170	86	34	44	2.1	M14×1.5	94.5	80.0	5.40
UC 317	85	180	96	40	46	3.0	M16×1.5	132.6	96.6	6.58
UC 318	90	190	96	40	48	3.0	M16×1.5	121.5	100.9	7.34
the bearings above can be supplied with any kinds of bearing housing										