



Bearing No.	Boundary Dimensions(mm)			Basic Load Rating(kN)		Speed Rating(r/min)		Weight (kg)
		D	B	Cr	Cor	Oil lubrication	Grease lubrication	
6003	17	35	10	6.80	3.35	28800	23900	0.040
6004	20	42	12	9.40	5.05	24200	20100	0.068
6005	25	47	12	10.1	5.85	20800	17300	0.079
6006	30	55	13	13.2	8.30	17600	14600	0.113
6007	35	62	14	16.0	10.3	15500	12900	0.149
6008	40	68	15	16.8	11.5	13900	11500	0.185
6009	45	75	16	21.0	15.1	12500	10400	0.231
6010	50	80	16	21.8	16.6	11500	9500	0.250
6011	55	90	18	28.3	21.2	10300	8500	0.362
6012	60	95	18	29.5	23.2	9700	8100	0.385
6013	65	100	18	30.5	25.2	9100	7600	0.430
6014	70	110	20	38.0	31.0	8300	6900	0.569
6015	75	115	20	39.5	33.5	7900	6600	0.603
6016	80	125	22	47.5	40.0	7300	6100	0.821
6017	85	130	22	49.5	43.0	7000	5800	0.848
6018	90	140	24	58.0	49.5	6500	5400	1.12
6019	95	145	24	60.5	54.0	6300	5200	1.18
6020	100	150	24	60.0	54.0	6000	5000	1.25
6021	105	160	26	72.5	65.5	5700	4700	1.60
6022	110	170	28	82.0	73.0	5400	4500	1.93
6203	17	40	12	9.60	4.60	26300	21800	0.065
6204	20	47	14	12.8	6.65	22400	18600	0.103
6205	25	52	15	14.0	7.85	19500	16200	0.127
6206	30	62	16	19.5	11.3	16300	13500	0.203
6207	35	72	17	25.7	15.3	14000	11600	0.287
6208	40	80	18	29.1	17.8	12500	10400	0.367
6209	45	85	19	32.5	20.4	11500	9500	0.416
6210	50	90	20	35.0	23.2	10700	8900	0.462
6211	55	100	21	43.5	29.2	9700	8100	0.607
6212	60	110	22	52.5	36.0	8800	7300	0.783
6213	65	120	23	57.5	40	8100	6700	0.990
6214	70	125	24	62.0	44.0	7700	6400	1.10
6215	75	130	25	66.0	49.5	7300	6100	1.20
6216	80	140	26	72.5	53.0	6800	5600	1.40
6217	85	150	28	83.5	64.0	6400	5300	1.80
6218	90	160	30	96.0	71.5	6000	5000	2.15
6219	95	170	32	109	82.0	5700	4700	2.60
6220	100	180	34	122	93.0	5400	4500	3.20
6221	105	190	36	133	105	5100	4200	3.71
6222	110	200	38	144	117	4800	4000	4.44

The bearings can be supplied with different precision level : P2 、 P4 、 P5, More details, please contact the company.